

## VALVOLA A FLUSSO AVVIATO PN16



## GLOBE VALVE ON-OFF TYPE PN16

## APPLICAZIONE:

Installazioni acqua, vapore e olio..

## APPLICATION:

Suitable for water, steam and oil.



## NORMA PROGETTO:

EN 1074

## SCARTAMENTO:

EN 558-1 Serie1

## FLANGE:

EN 1092-2

## COLLAUDI:

EN 12266

## TEMP. ESERCIZIO:

≤200°C

## DESIGN STANDARD:

EN 1074

## FACE TO FACE:

EN 558-1 Serie1

## FLANGES:

EN 1092-2

## TESTS:

EN 12266

## WORKING TEMP.:

≤200°C

DENOMINAZIONE PART	MATERIALI MATERIALS
1 CORPO BODY	GJL 250 GJL 250
2 TENUTA CORPO BODY SEAL RING	ACCIAIO INOX STAINLESS STEEL
3 TENUTA DISCO DISC SEAL RING	ACCIAIO INOX STAINLESS STEEL
4 DISCO DISC	GJL 250 GJL 250
5 ASSE STEM	ACCIAIO INOX STAINLESS STEEL
6 GUARNIZIONE GASKET	GRAFITE GRAPHITE
7 CAPPELLO BONNET	GJL 250 GJL 250
8 VITE E DADO BOLT & NUT	ACCIAIO ZINCATO GALVANIZED STEEL
9 GUARNIZIONE GASKET	GRAFITE GRAPHITE
10 PREMISTOPPA PACKING GLAND	GJL 250 GJL 250
11 VOLANTINO HANDWHEEL	GJL 250 GJL 250

DN	D	K	G	b	n-ød	L	H	M	W(kg)
15	95	65	47	14	4-14	130	160	80	3.4
20	105	75	58	16	4-14	150	165	80	3.8
25	115	85	68	16	4-14	160	190	100	5.1
32	140	100	78	18	4-18	180	210	120	8
40	150	110	88	18	4-18	200	220	140	9.4
50	165	125	102	20	4-18	230	235	140	11.4
65	185	145	122	20	4-18	290	275	160	18
80	200	160	138	22	8-18	310	335	240	30.7
100	220	180	158	24	8-18	350	375	240	40
125	250	210	188	26	8-18	400	425	280	62
150	285	240	212	26	8-22	480	490	320	91
200	340	295	268	30	12-22	600	620	360	153

COLORE: Grigio RAL 7015.

COLOUR: Grey RAL 7015.